
Technical Data Sheet

Blocking width:	GES-2 up to 2000 mm GES-3 up to 3000 mm GES-4 up to 4000 mm
Casing dimensions:	Width: 350 mm Height: 1100 mm Depth: 365 mm
Blocking width:	GES-5 up to 5000 mm GES-6 up to 6000 mm GES-7 up to 7000 mm GES-8 up to 8000 mm
Casing dimensions:	Width: 460 mm Height: 1100 mm Depth: 470 mm
	For blocking width greater than 3,00 m it is necessary to install an impact post or a pendulum support for functional function.
Drive:	400 V three-phase motor (GES 2-4 ONLY in combination with heating) (Boom arm options –for all CW’s- such as skirts ONLY possible with GES 7-8 motor
Gearing:	worm gear motor
Auto-stop:	by magnetic switch, contact free, freeze proof
Drive control:	microprocessor-control; WE-Tronic II
Casing:	stainless-steel 1.4301, grinding 340, cover rounded, red 3002, optional powder coated
Barrier pole:	aluminium-round-pole GES 2 – 4, diameter 80 mm aluminium-round-pole GES 5 – 8, diameter 100 mm powder coated, colour white (RAL 9016) with red strips.
Control:	optional with key switch, desk-top console, radio control, code-card reader, induction loop, photo-electric barrier.
Options:	pendulum support, impact post, crawl-under protection, safety pressure strips, traffic-light, intercom system, boom breaking point, operating post.