



Aluminium sliding gate **EntraLight**

Sturdy and smooth running sliding gate





Smooth running aluminium sliding gate

The type-tested EntraLight aluminium sliding gate offers a particularly high stability combined with lightweight construction - even with large opening widths. Silver-coloured anodised aluminium and powder coating in different RAL colours allow individual adaptation of the

classic gate design. EntraLight features easy and time-saving installation due to ready-to-install gate units. In addition, this gate convinces with long-term functionality, reliability and are low maintenance. The WE-Tronic Light control unit offers a large number of potential contacts simplifying

the connection of control devices on site such as fire alarm systems, card readers, keypads, alarm systems and more. Also in terms of serviceability the control unit achieves plus-points because of their simple and easy programming and setting of desired parameters.





ENTRALIGHT	
HEIGHT	1050 - 2050 mm*
CLEAR OPENING WIDTH	4000 - 8000 mm
BAR INFILL	Square tube 40 mm, Spacing max. 120 mm
PROFILES	Standard profiles
DRIVE UNIT	Electric drive with covered, profile integrated, spring-loaded toothed rack**
CONTROL UNIT	WE-Tronic Light
OPERATING TEMPERATURE	From -20°C up to +60°C
CERTIFICATIONS	Type-tested by German TÜV according to DIN EN 13241-1 High safety standards according to DIN EN 12453
OPTIONS	Remote control, table buttons, anti-climbing device, floor plates, key safe, locking device, etc.

* Including 100 mm ground clearance

** For power operated version





EntraLight from Werra

In the electric version of course

type-tested according to DIN EN 13241-1!



Perimeter Protection Germany GmbH
Johann-Reineke-Straße 6-10
33154 Salzkotten, Germany
Tel.: +49 (0) 5258 500 70
E-Mail: info@perimeterprotection.net
www.perimeterprotection.net



ID-55.2.19001

Versions may include optional equipment. Technical details are subject to change.