



# Quick folding gate **EntraQuick® I & II**

The smart combination of gate and barrier





### Type-tested, cantilevered state-of-art quick folding gate

The TÜV type-tested, fully cantilevered quick folding EntraQuick® offers full-height perimeter protection in closed position and unobstructed security for each entry or exit situation due to its trackless design. Its extremely high speed allows a quick closing after each passage, to efficiently support smooth workflows in everyday operation! Furthermore no run back area is required. Due to its solid bar infill and the ingenious lever kinematics EntraQuick® is particularly stable and doesn't require an additional floor lock in closed position. EntraQuick® can be installed easily and quickly thanks to pre-assembled drive post and folding leaf unit. It is driven by two AC motors. The gate leaves fold open inwards towards the secure site and with an (optional) additional control each leaf can be opened separately if required. EntraQuick® is a perfect substitute for combined gate and barrier installation at access points. There are two models available in different heights and opening widths.





	ENTRAQUICK® I	ENTRAQUICK® II
HEIGHT	2,05 m, 2,45 m	2,05 m, 2,55 m, 3,05 m
CLEAR OPENING WIDTH	3 - 6 m in 500 mm increments	4 - 8 m in 500 mm increments
INFILL	Bar infill	
PROFILES	Standard profiles	
FOUNDATIONS	Top edge of foundation 200 mm below finished floor level	
DRIVE UNIT	AC motor	
CONTROL UNIT	Multifunctional, automatic control unit WE-Tronic II with integrated frequency converter	
INTERLOCKING	Via reception fork and in-feed roller	Via drive mechanism supported by interlocking of gate leaves through reception fork and in-feed roller
OPERATING TEMPERATURE	-20°C bis +60°C	
CERTIFICATIONS	TÜV type-tested according to DIN EN 13241-1 and EC-Machine-Directive 2006/42/EG	
OPTIONS	Floodlight, remote control, rotating beacon, safety edges and induction loops, 230 V AC motor, various colours, LED lighting for the realisation of a traffic light system	

\* For a CWO of 10 m the maximum height is 2.05 m





### Optimum protection through proper combination

Depending on requirements with pedestrian separation, vehicles and people. This solution is ideal for protecting against terrorist attacks and guarantees a high level of protection. In combination with the vehicle barriers EntraQuick® and TurnSec turnstile from Werra offers an immediate closure against forceful entry of

Perimeter Protection Germany GmbH  
Johann-Reineke-Straße 6-10  
33154 Salzkotten, Germany  
Tel.: +49 (0) 5258 500 70  
E-Mail: [info@perimeterprotection.net](mailto:info@perimeterprotection.net)  
[www.perimeterprotection.net](http://www.perimeterprotection.net)



ID-55.2.24011

Versions may include optional equipment. Technical details are subject to change.